



Bulletin of the Mineral Research and Exploration

<http://bulletin.mta.gov.tr>



Determination of Atterberg Limits using the vane shear test method

Kamil KAYABALI^{a*}, H. B. NAGARAJ^b, Deniz YILMAZ^a and Muhammet BEYHAN^a

^a Ankara University, School of Engineering, Geological Engineering Department, Ankara, Türkiye

^b B.M.S College of Engineering, Bangalore, India

Research Article

Keywords:

Liquid Limit, Plastic Limit, Undrained Shear Strength, Vane Shear Test, Atterberg Limits.

ABSTRACT

Atterberg limits are important index parameters used to classify soils for various engineering applications. Engineering properties of soils are predicted through simple correlations with index properties and thereby the engineering behavior of soils are qualitatively assessed. There are two popular methods of determining liquid limit, and plastic limit is commonly determined adopting rolling thread methods. To avoid operator related variations in determining plastic limit by conventional method, some researchers have explored using cone method as an alternative. However, there is no consensus about the depth of penetration to reckon the end of plastic state. Though various other test methods have been developed to determine plastic limit (like roll plate device), cone penetration with its limitation of determining plastic limit, is the only method to determine both liquid and plastic limit of soils. Since laboratory vane shear test is a simple and reliable method of determining undrained strength of fine-grained soils, the authors have explored to determine both liquid and plastic limits through correlations developed between undrained strength and water content over a range of consistencies between liquid and plastic states. This would eliminate determining liquid and plastic limit separately without sacrificing the reliability of results.

Received Date: 14.12.2022

Accepted Date: 18.09.2023

1. Introduction

Atterberg's original proposal for consistency limits (Atterberg, 1911) included seven qualitative limits, of which only two found more common usage in geotechnical engineering, namely liquid limit (LL) and plastic limit (PL). LL is the water content at which the soil starts to flow under its own weight. PL is the onset of soil brittleness or the water content corresponding to the transition from plastic- to semi-solid state.

The LL and PL, either individually or in the form of plasticity index (PI) have been used in a number of empirical correlations and can be helpful for preliminary estimates in the early stages of

design. Such applications include classification of soils (Feng, 2004a), prediction of engineering properties like undrained shear strength (Skempton, 1954), consolidation parameters [e.g., the coefficient of compression, coefficient of recompression, preconsolidation pressure, settlement (Terzaghi and Peck, 1967; Azzouz et al., 1976; Leonards, 1976; Nagaraj and Srinivasa Murthy, 1986)], and determination of soil penetration resistance (Stroud, 1974) and the like.

The most common techniques to determine the liquid limit are the Casagrande cup and cone penetration test; and plastic limit are the thread rolling methods. Determination of LL by the Casagrande cup

Citation Info: Kayabali, K., Nagaraj, H. B., Yılmaz, D., Beyhan, M. 2024. Determination of Atterberg Limits using the vane shear test method. Bulletin of the Mineral Research and Exploration 174, 1-10. <https://doi.org/10.19111/bulletinofmre.1362349>

*Corresponding author: Kamil KAYABALI, kayabali@ankara.edu.tr

method involves a number of uncertainties (see, for instance, Wroth and Wood, 1978; Lee and Freeman, 2007; Kayabali and Tüfenkçi, 2010a). The fall cone method is advantageous in comparison with Casagrande's method as it has less operator dependent variations and has good reproducibility of results. It also gives much lower standard deviation of the results than the cup test when identical samples are tested at multiple laboratories (Sherwood and Ryley, 1970; Haigh, 2012). Thus, there is not much debate on the uncertainties of fall cone tests. However, determination of plastic limit by the thread rolling method has always been a point of concern due to its operator related variations. Hence, a number of attempts have been made to determine the plastic limit using the fall cone method. Some of such attempts include the works of Towner (1973), Campbell (1976, 1983), Wood and Wroth (1978), Campbell et al. (1980), Feng (2000, 2001), Belviso et al. (1985), Rao (1987), Harison (1988), Sharma and Bora (2003), Feng (2004a,b), Al-Dahlaki and Al-Sharify (2008), Rashid et al. (2008), Lee and Freeman (2009), Sivakumar et al. (2009, 2014). Shimobe (2010), using various types of cones, concluded that the extended fall cone method is capable of simultaneously determining both the liquid and plastic limits. He further stated that the fall cone test can also be used to determine the liquidity index as a state quantity, the undrained shear strength, and sensitivity of soils in terms of the cone penetration. Extrusion method was also employed as a tool to determine the consistency limits of fine-grained soils. Timar (1974), using the direct extrusion method, obtained partial success towards determining the two most common consistency limits. Whyte (1982), based on the results of preliminary reverse extrusion (RX) tests on a low plasticity clay, showed that RX is a reliable method for determining soil plasticity; also, that it is simple, rapid and economical. Kayabali and Tüfenkçi (2010b) showed that the RX test can provide a reasonable degree of success in determining LL and PL and that the RX test eliminates most of the uncertainties involved in both the conventional PL and LL tests, most importantly those that are operator dependent. Kayabali et al. (2016) developed a testing apparatus called the mud press machine (MPM). Using the test results of 275 soil samples, the authors of the study showed that Atterberg limits can be

determined in a more rational and quantifiable basis using the MPM.

Vane shear test is one of the most common tools to assess the undrained shear strength of cohesive soils. It can be employed both in the laboratory and in the field. It was originated in Sweden in the early 1900s and became popular towards 1940s. Major advantages of the test are: ease to conduct, simplicity, robustness and speed. It also allows the measurement of peak and residual strength, and therefore, the sensitivity of cohesive soils. It provides an indirect assessment of over-consolidation ratio of a soil deposit as well (Ameratunga et al., 2016). It is recommended to be used on soils with an undrained shear strength less than 100 kPa (American Society of Testing Materials, 2000). The miniature vane test employing four springs with different stiffnesses is capable of measuring undrained shear strength of soils from a few kPa to about 100 kPa, which is the common range for the plastic behavior between the liquid and the plastic limit of fine-grained soils.

Kyambadde (2010) stated that, although VST is not the most attractive method, it provides a degree of validation of liquid limit data where vane shear strength relationships are available.

The scope of this investigation is to illustrate the usability of miniature vane shear test to determine the two major Atterberg limits.

2. Materials and Methods

One hundred soil samples were subjected to Atterberg limits and vane shear tests. Majority of the soil samples used in the study were residual soils produced by weathering of igneous rocks and few soils were lacustrine deposits obtained in the vicinity of Ankara, Türkiye. The soils selected to be used in this study were such that they had a wide range of plasticity. The liquid limits ranged from 23 to 106, and the plasticity index ranged from 7.5 to 50. The positions of soil samples on the plasticity chart are presented in Figure 1.

The various equipment employed for this experimental research includes a fall-cone, a roll-plate device (Figure 3) and a miniature vane shear apparatus

which are respectively shown in Figures 2 to 4. The device for the vane shear test (Figure 4) measures the torque by electronic transducers instead of by springs. It facilitates measurement of torque up to 3.0 N.m. The measurable shear stress using this servo-controlled




Figure 1- Positions of soil samples on the Casagrande chart.



Figure 4- Miniature vane shear test device.

VST device ranges from 0.1-466 kPa when the blade dimensions are 12.7 mm x 12.7 mm. The rotational speed ranges from 0.001-1200 degrees per minute.



Figure 2- The fall cone device used in this investigation.



Figure 3- Roll-plate device for plastic limit tests.

All soil specimens were first sieved through an ASTM#40 mesh (American Society for Testing Materials, 2005). Then, sufficient quantity of water was added and the soil was mixed thoroughly before transferring into polythene covers. The mixed soil samples in polythene covers were properly labelled, and were placed in desiccator filled with water at the bottom to maintain 100% humidity. The samples were left for at least 20 h for proper saturation. For each of the soil samples the liquid limit was determined by using a fall-cone device (BS1377-1990). At least five trial points were obtained by varying the water content from dry side to wet side and the corresponding cone penetration was recorded. The range of cone penetration was targeted to be between 15 mm to 25 mm. Water content corresponding to 20 mm penetration was reckoned as the liquid limit of soil (British Standards Institution, 1990). Plastic limit of all the soils was evaluated as per the standard procedure outlined in ASTM D4318-05 Standard (American Society for Testing Materials, 2005) using the roll-plate device. Tests were repeated at least 5 times and the average of five plastic limit tests was taken to represent the soil subjected to the roll-plate test. The test results of liquid limit and plastic limit of all the soils are tabulated in Table 1.

Table 1- The results of Atterberg Limits tests and vane shear tests (LL: liquid limit, PL: plastic limit, PI: plasticity index, USCS: Unified Soil Classification System, a and b: coefficients obtained from the curve fitted to the semi-logarithmic experimental curve of the vane shear test, R²: the regression coefficient, ML: silt of low plasticity, MH: silt of high plasticity, CL: clay of low plasticity, CH: clay of high plasticity).

No.	LL	PL	PI	USCS	a	b	R ²
1	51.1	35.9	15.2	MH	2E+08	0.377	0.976
2	63.0	44.2	18.8	MH	5.E+07	0.287	0.970
3	77.2	44.6	32.6	MH	14909	0.118	0.976
4	32.4	19.3	13.1	CL	12109	0.271	0.988
5	60.4	37.0	23.4	MH	5968	0.109	0.986
6	43.3	25.8	17.5	CL	44731	0.246	0.988
7	41.0	28.0	13.0	ML	163178	0.275	0.950
8	40.0	26.9	13.1	ML	211404	0.288	0.988
9	47.1	29.4	17.7	ML	21980	0.187	0.980
10	41.7	25.6	16.1	CL	63439	0.259	0.991
11	37.0	23.7	13.3	CL	8959	0.242	0.998
12	42.9	25.4	17.5	CL	17698	0.219	0.990
13	36.2	21.6	14.6	CL	16136	0.25	0.985
14	44.5	26.3	18.2	CL	31014	0.228	0.999
15	51.3	30.5	20.8	MH	8595	0.145	0.978
16	36.0	23.3	12.7	CL	24575	0.255	0.998
17	35.0	22.5	12.5	CL	32018	0.26	0.998
18	41.0	23.9	17.1	CL	96358	0.277	0.993
19	23.3	15.8	7.5	CL	26556	0.323	0.998
20	52.0	29.2	22.8	MH	16740	0.169	0.922
21	86.5	47.6	38.9	MH	6093	0.086	0.966
22	46.0	25.9	20.1	CL	7303	0.166	0.985
23	39.6	22.1	17.5	CL	14016	0.226	0.992
24	45.4	24.0	21.4	CL	6445	0.175	0.998
25	65.6	37.2	28.4	MH	171511	0.192	0.972
26	75.4	40.9	34.5	MH	8817	0.112	0.992
27	72.9	44.9	28.0	MH	5341	0.096	0.971
28	103	62.2	40.8	MH	7639	0.074	0.943
29	41.7	26.3	15.4	ML	22955	0.22	0.997
30	46.1	29.0	17.1	ML	83707	0.246	0.981
31	54.1	33.7	20.4	MH	20170	0.166	0.997
32	56.1	33.6	22.5	MH	88339	0.214	0.996
33	51.5	31.2	20.3	MH	25663	0.192	0.978
34	74.7	43.9	30.8	MH	916	0.058	0.915
35	45.0	24.6	20.4	CL	7024	0.174	0.996
36	68.6	42.8	25.8	MH	34188	0.135	0.967
37	58.2	39.5	18.7	MH	54624	0.163	0.995
38	60.0	39.8	20.2	MH	344266	0.205	0.983
39	50.4	23.1	27.3	CH	3019	0.149	0.990

Table 1- Continued.

No.	LL	PL	PI	USCS	a	b	R ²
40	51.0	30.1	20.9	MH	104103	0.214	0.967
41	95.0	52.1	42.9	MH	2731	0.073	0.996
42	85.0	46.9	38.1	MH	3649	0.084	0.989
43	73.5	46.9	26.6	MH	120860	0.154	0.970
44	71.1	46.0	25.1	MH	11807	0.116	0.990
45	77.8	49.4	28.4	MH	1.E+06	0.174	0.991
46	101	62.2	38.3	MH	922631	0.145	0.934
47	48.9	35.7	13.2	ML	1.E+06	0.263	0.998
48	36.8	19.3	17.5	CL	3165	0.191	0.992
49	33.8	18.8	15.0	CL	6551	0.233	0.992
50	32.0	18.8	13.2	CL	24462	0.311	0.996
51	65.3	31.0	34.3	CH	2761	0.116	0.997
52	57.2	35.4	21.8	MH	56743	0.186	0.976
53	41.6	27.4	14.2	ML	6773	0.165	0.997
54	49.0	33.0	16.0	ML	883887	0.259	0.997
55	44.1	26.8	17.3	ML	75389	0.235	0.993
56	53.5	25.6	27.9	CH	8660	0.171	0.981
57	33.1	19.8	13.3	CL	10956	0.26	0.997
58	38.7	23.8	14.9	CL	1979	0.159	0.999
59	37.5	21.8	15.7	CL	4517	0.208	0.997
60	53.0	31.3	21.7	MH	81326	0.211	0.994
61	54.0	33.7	20.3	MH	424	0.067	0.941
62	85.1	41.1	44.0	MH	10705	0.108	0.986
63	62.9	37.4	25.5	MH	35110	0.161	0.996
64	55.8	30.4	25.4	MH	24486	0.178	0.987
65	38.5	24.1	14.4	CL	1922	0.161	0.993
66	44.1	28.9	15.2	ML	62961	0.229	0.994
67	63.4	37.1	26.3	MH	9868	0.133	0.991
68	44.3	26.8	17.5	ML	45369	0.222	0.991
69	55.0	31.3	23.7	MH	14609	0.159	0.989
70	51.1	29.6	21.5	MH	18762	0.174	0.993
71	52.0	33.9	18.1	MH	2.E+06	0.275	0.987
72	41.0	24.6	16.4	CL	62589	0.261	0.996
73	37.9	23.2	14.7	CL	2567	0.178	0.995
74	65.1	39.2	25.9	MH	164541	0.184	0.986
75	50.2	29.9	20.3	MH	26825	0.194	0.984
76	63.7	41.4	22.3	MH	8.E+06	0.258	0.980
77	40.9	26.0	14.9	ML	136616	0.281	0.988
78	50.9	32.5	18.4	MH	36741	0.191	0.998
79	71.8	36.4	35.4	MH	283563	0.202	0.984

Table 1- Continued.

No.	LL	PL	PI	USCS	a	b	R ²
80	53.1	34.6	18.5	MH	853309	0.247	0.986
81	47.8	28.6	19.2	ML	18210	0.181	0.977
82	52.9	26.7	26.2	CH	5226	0.149	0.984
83	86.5	61.5	25.0	MH	174311	0.127	0.996
84	106	73.8	32.4	MH	49136	0.092	0.997
85	91.7	46.4	45.3	MH	1707	0.072	0.960
86	51.4	30.9	20.5	MH	9713	0.16	0.993
87	102	66.7	35.1	MH	39473	0.098	0.995
88	70.9	43.2	27.7	MH	4576	0.108	0.985
89	24.6	14.4	10.2	CL	9276	0.353	0.999
90	25.1	14.4	10.7	CL	4485	0.271	0.978
91	74.0	37.7	36.3	MH	2981	0.094	0.992
92	79.8	38.6	41.2	MH	4561	0.101	0.992
93	85.8	41.7	44.1	MH	2371	0.085	0.990
94	86.9	42.4	44.5	MH	5409	0.097	0.989
95	88.0	43.1	44.9	MH	3884	0.088	0.991
96	90.2	44.4	45.8	MH	2425	0.078	0.995
97	90.8	45.3	45.5	MH	4599	0.089	0.997
98	92.8	46.7	46.1	MH	2475	0.075	0.996
99	90.0	47.9	42.1	MH	4725	0.084	0.990
100	98.0	48.2	49.8	MH	1905	0.067	0.993

The vane shear tests were performed in accordance with the ASTM D4648-00 Standard (American Society of Testing Materials, 2000). Each of the soils used in the study was prepared in a similar way as done for the liquid limit and plastic limit test. The test procedure involved conducting five trials of vane shear tests using the saturated soil having a consistency between the liquid limit and plastic limit. The measured torques were converted to undrained shear strengths using the relationships given in Equations 1 and 2 (American Society of Testing Materials, 2000):

$$T = \tau \times K \tag{1}$$

$$K = \frac{\pi D^2}{2 \times 10^6} \left[1 + \frac{D}{3H} \right] \tag{2}$$

where T = torque (N.m), τ = undrained shear strength (N/m²), K = vane blade constant (m³), D = measured diameter of the vane (mm) and H = measure height of the vane (mm). The measured undrained shear strengths with respective water contents were plotted in a semi-logarithmic plot. One such typical plot

for soil No. 58 is shown in Figure 5, from which an equation was obtained in the following form:

$$y = a \exp^b \tag{3}$$

where y is the undrained shear strength (s_u) and a and b are the regression coefficients.




Figure 5- A sample plot constructed upon VST test results.

3. Experimental Results

From Table 1, it can be seen that of the 100 samples collected from different locations, 57 soils are classified as MH (silt of high plasticity), 26 are classified as CL (clay of low plasticity), 13 as ML (silt of low plasticity) and 4 as CH (clay of high plasticity). Thus, the soils covered a wide range of plasticities. As mentioned earlier, each soil sample was subjected to five vane shear tests at different water contents. Thus, the resulting number of undrained shear strength and water content pairs is 500 for 100 soil samples. Listing of such a large data occupies a great deal of space; so, to save space, the results of vane shear tests are presented only in terms of a and b coefficients as presented in Table 1.

In order to explore for a possible correlation between undrained shear strengths obtained from the miniature vane shear test and Atterberg limits, the numerical data presented in Table 1 was subjected to a series of statistical analyses. To show if it was possible to determine the liquid limit in terms of the undrained shear strength and water content, a multiple regression analysis was performed using the software DATAFIT (DATAFIT, 2008). This way a series of both complex and rather simple empirical equations were obtained defining the LL in terms of s_u and w . One of the simplest of such relationships are selected and provided as follows:

$$LL = 0.902 (w^{0.997}) s_u^{0.138} \quad (R^2 = 0.92) \quad (4)$$

where s_u is in kPa and w is in %. The maximum coefficient of correlation was 0.95 for highly complex polynomial equations which involved many constants. As a next step, Equation (4) was employed to predict the liquid limit empirically. Figure 6 is a plot of the empirically-predicted liquid limits with those determined experimentally using the fall-cone method. The deviations from the measured liquid limits were evaluated statistically in terms of absolute percent errors. Figure 7 is the histogram of absolute percent errors of the measured liquid limits when determining the liquid limit using the predictive Equation 4. The overall absolute percent error is 6.8%. A quick glimpse on Figure 7 reveals that the amount of error for the predicted liquid limits of 80% of all soils is within $\pm 10\%$.




Figure 6- Comparison between the predicted liquid limits versus the measured liquid limits.




Figure 7- Histogram of absolute errors of predicted liquid limits.

Similarly, 500 sets of water content, undrained shear strength and plastic limit were also subjected to a multiple regression analysis to predict the plastic limit in terms of water content and undrained shear strength. The following simple version of the empirical equation was obtained:

$$PL = 0.609 (w^{0.959}) s_u^{0.139} \quad (R^2 = 0.95) \quad (5)$$

In the next step, Equation (5) was employed to predict the plastic limit empirically. Figure 8 is a plot of the empirically-predicted plastic limits with those determined experimentally using the roll-plate method. The deviations from the measured plastic limits were evaluated statistically in terms of absolute percent errors. Figure 9 is the histogram of absolute percent errors of the measured plastic limits when determining the plastic limit using the predictive Equation 5. The overall absolute percent error is 5.3%.




Figure 8- Comparison between the predicted plastic limits versus the measured plastic limits.




Figure 9- Histogram of absolute errors of predicted plastic limits.

A quick glimpse on Figure 9 reveals that the amount of error for the predicted plastic limits of 86% of all soils is within $\pm 10\%$.

Equations 4 and 5 are found very useful in that they can be used to predict the two Atterberg limits, namely the liquid limit and plastic limit based on a single trial of VST test which is done at any water content between plastic limit and liquid limit. To avoid error introduced by a single trial of VST test in predicting liquid and plastic limits, it is better to use the results of at least a few trials of vane shear tests conducted at different water contents between PL and LL, so that the coefficients a and b are obtained.

The coefficients a and b as presented in Table 1 for each soil sample were also subjected to multiple regression analyses along with the Atterberg limits data. One hundred sets of a and b coefficients and the

liquid limit yield the following short version of the predictive equations:

$$LL = 3.62 (a^{0.106}) b^{-0.92} \quad (R^2 = 0.92) \quad (6)$$

Similarly, plastic limit is defined in terms of a and b coefficients:

$$PL = 1.72 (a^{0.129}) b^{-0.91} \quad (R^2 = 0.92) \quad (7)$$

The overall absolute percent error between the measured and predicted the liquid limits is 6.3% and that for plastic limit, it is 3.9%, which implies that the Atterberg limits are predicted with a slightly higher degree of accuracy than those predicted by Equations 4 and 5 which make use of water content and undrained shear strength.

4. Results

In order to eliminate determining the liquid and plastic limit separately without sacrificing the reliability of estimating these limiting water contents, the authors have explored to determine both these limits using a laboratory vane shear test through the correlations developed between the undrained strength and water content over a range of consistency between the liquid and plastic states. From the vane test results of 100 natural soils used in this study having a wide range of plasticity properties, attempts to do a multi regression analysis of the two empirical coefficients a and b (obtained from the undrained strength versus water content of individual soils) with the LL and PL led to two separate correlation equations to empirically predict the LL and PL with the undrained strength and water content in terms of the empirical coefficients. Even a single test data from vane shear test at a water content between LL and PL can be just sufficient to predict LL and PL respectively using the correlation Equations 4 and 5. However, to improve the efficiency of predicting LL and PL, one can use the results of at least a few trials of vane shear tests conducted at different water contents between PL and LL, so that, the coefficients a and b are obtained. These coefficients can be used to predict LL and PL respectively using the correlation Equations 6 and 7. The developed correlations becomes handy to have an independent and quick check on the test results of LL and PL while handling large data generated at soil laboratories.

References

- Al-Dahlaki, H., Al-Sharify, G. A. 2008. A proposed approach for plastic limit determination using the drop-cone penetrometer device. *Journal of Engineering and Development* 12(1), 107–117.
- Ameratunga, J., Sivakugan, N., Das, B. M. 2016. *Correlations of soil and rock properties in geotechnical engineering*. Springer India, 228 p.
- American Society of Testing Materials, 2000. Standard test method for laboratory vane shear test for saturated fine-grained soil. ASTM D4648-00, West Conshocken, PA, USA.
- American Society for Testing Materials, 2005. Standard test methods for liquid limit, plastic limit, and plasticity index of soils. ASTM D4318-05, West Conshohocken, PA.
- Atterberg, A. 1911. Lerornas forhallande till vatten, deras plasticitetsgranser och plasticitetsgrader. *Kungliga Lantbruk sakademiens Handlingar och Tidskrift* 50(2), 132–158 (in Swedish).
- Azzouz, A. S., Krizek, R. J., Corotis, R. B. 1976. Regression analysis of soil compressibility. *Soils and Foundations* 16(2), 19-29.
- Belviso, R., Ciampoli, S., Cotecchia, V., Federico, A. 1985. Use of the cone penetrometer to determine consistency limits. *Ground Engineering* 18(5), 21–22.
- British Standards Institution, 1990. *British standard methods of test for soils for engineering purposes, BS 1377*. Milton Keynes, British Standards Institution.
- Campbell, D. J. 1976. Plastic limit determination using a drop cone penetrometer. *Soil Science* 27(3), 295–300.
- Campbell, D. J. 1983. Discussion. *Geotechnique* 33(1), 78–79.
- Campbell, D. J., Stafford, J. V., Blackwell, P. S. 1980. The plastic limit as determined by the drop cone test in relation to the mechanical behavior of soil. *European Journal of Soil Science* 31, 11-24.
- DATAFIT, 2008. *Datafit Version 9.0.59*, Oakdale Engineering, RC 101, 23 Tomey Road, Oakdale, PA, 15071 USA.
- Feng, T. W. 2000. Fall-cone penetration and water content relationships of clays. *Geotechnique* 50(2), 181-187.
- Feng, T. W. 2001. A linear log d -log w model for the determination of consistency limits of soils. *Canadian Geotechnical Journal* 38(6), 1335-1342.
- Feng, T. W. 2004a. Using a small ring and a fall-cone to determine the plastic limit. *Journal of Geotechnical and Geoenvironmental Engineering* 130(6), 630-635.
- Feng, T. W. 2004b. Determining the consistency limits of high plasticity clays by the BS fall cone method. *Ground Engineering* 37(4), 56-57.
- Haigh, S. K. 2012. Mechanics of the Casagrande liquid limit test. *Canadian Geotechnical Journal* 49, 1015-1023.
- Harison, J. A. 1988. Using the BS cone penetrometer for the determination of the plastic limit of soils. *Geotechnique* 38(3), 433–438.
- Kayabali, K., Tüfenkçi, O. O. 2010a. Shear strength of remolded soils at consistency limits. *Canadian Geotechnical Journal* 47(3), 259-266.
- Kayabali, K., Tüfenkçi, O. O. 2010b. Determination of plastic and liquid limits using the reverse extrusion technique. *Geotechnical Testing Journal* 33(1), 14-22.
- Kayabali, K., Aktürk, O., Fener, M., Özkeser, A., Üstün, A. B., Dikmen, O., Harputlugil, F. H., Asadi, R. 2016. Determination of Atterberg limits using newly devised mud press machine. *Journal of African Earth Sciences* 116, 127-133.
- Kyambadde, B. S. 2010. Determination of strength and index properties of fine-grained soils using a soil minipenetrometer. PhD Thesis, University of Brighton 292 p.
- Lee, L. T., Freeman, R. B. 2007. An alternative test method for assessing consistency limits. *Geotechnical Testing Journal* 30(4), 1–8.
- Lee, L. T., Freeman, R. B. 2009. Dual-weight fall cone method for simultaneous liquid limit determination. *Journal of Geotechnical and Geoenvironmental Engineering* 135(1), 158–161.
- Leonards, G. A. 1976. Estimating consolidation settlements of shallow foundations on overconsolidated clays. Special Report 163, Transportation Research Board, 13-16.
- Nagaraj, T. S., Srinivasa Murthy, B. R. 1986. A critical reappraisal of compression index. *Geotechnique* 36(1), 27-32.
- Rao, H. Y. 1987. Determination of Atterberg limits by cone penetrometer. *International Proceeding of 8th Asian Regional Conference on Soil Mechanics and Foundation Engineering* 1, 81–84.
- Rashid, A. S. A., Kassim, K. A., Katimon, A., Noor, N. M. 2008. Determination of plastic limit of soil using modified methods. *Malaysian Journal of Civil Engineering* 20(2), 295–305.
- Sharma, B., Bora, P. K. 2003. Plastic limit, liquid limit and undrained shear strength of soil - reappraisal. *Journal of Geotechnical and Geoenvironmental Engineering* 129(8), 774-777.

- Sherwood, P. T., Ryley, M. D. 1970. An investigation of a cone penetrometer method for the determination of the liquid limit. *Geotechnique* 20(2), 203-208.
- Shimobe, S. 2010. Determination of index properties and undrained shear strength of soils using the fall cone test. *Proceedings of the 7th International Symposium on Lowland Technology*, September 16-18, Saga, Japan, 51-59.
- Sivakumar, V., Glynn, D., Cairns, P., Black, J. A. 2009. A new method of measuring plastic limit of fine materials. *Geotechnique* 59(10), 813-823.
- Sivakumar, V., O'Kelly, B. C., Henderson, L., Moorhead, C., Chow, S. H. 2014. Measuring the plastic limit of fine soils. An experimental study. *Proceedings of Institution of Civil Engineers* 168(GE1), 53-64.
- Skempton, A. W. 1954. Discussion – sensitivity of clays and the c/p ratio in normally consolidated clays. *Proceedings of the American Society of Civil Engineers*, Separate 478, 19-22.
- Stroud, M. A. 1974. The Standard Penetration Test in sensitive clays and soft rocks. *International Proceeding of European Seminar on Penetration Testing*, Stockholm, 2(2), 366-375.
- Terzaghi, K., Peck, R. B. 1967. *Soil mechanics in engineering practice*. John Wiley and Sons 2nd Ed., 729 p.
- Timar, A. 1974. Testing the plastic properties of cohesive and intermediate-type soils by extrusion. *Acta Technica Academiae Scientiarum Hungaricae* 76(3-4), 355-370.
- Towner, G. D. 1973. An examination of the fall cone method for the determination of some strength properties of remoulded agricultural soils. *Journal of Soil Science* 24(4), 470-479.
- Whyte, I. L. 1982. Soil plasticity and strength - a new approach using extrusion. *Ground Engineering* 15(1), 16-24.
- Wood, D. M., Wroth, C. P. 1978. The use of the cone penetrometer to determine the plastic limit of soils. *Ground Engineering* 11(3), 37.
- Wroth, C. P., Wood, D. M. 1978. The correlation of index properties with some basic engineering properties of soils. *Canadian Geotechnical Journal* 15(2), 137-145.